

FEATURES & BENEFITS

CONSTRUCTION

FDA high-density green polyethylene tank provides the light and durable construction required in a portable unit.

FLOW CONTROLS

Pulling down the eyewash arm will begin flushing the 9 gallon portable tank at .4 gpm (2) for about 15 minutes, which in turn will create a full patterned flushing of the eyes. Positive upper limits stop the flow of water while covering and protecting the spray outlets when not in use.

DESIGN

Tank comes complete with a wide-fill opening and threaded cap for quick inspection, cleaning, and filling. Unit also comes equipped with top and side handles making relocation simple.

MOUNTING

J-shaped stainless steel wall bracket makes for a well constructed portable mount for easy removal and re-mount.

SAFETY

Clearly depicted emergency eyewash sign and supplied bottle of bacteriostatic additive decrease the possibility of mishaps and make for a safer piece of emergency equipment.

OPTIONS

- ❑ Cart: Model 9008 cart is designed to transport models 7601.37, 7500, or 7501 portable eyewashes, and the 9009 wastewater container. Unit is constructed of heavy-duty 1" tubular frame with green powder-coated finish and equipped with four solid rubber wheels.
- ❑ Waste Water Container: Model 9009 is a twenty-gallon wastewater container constructed of tough yellow polymer resin. Unit is used to collect water during weekly testing of emergency equipment.
- ❑ Bacteriostatic Additive: Model 9082, bacteriostatic preservative for use in portable eyewash stations. One 8 oz. (237 ml) bottle will preserve 6 to 20 gallons of portable water for up to six months. Four bottles per carton.

To see all options for this model, visit www.hawsc.com



SPECIFICATIONS

Model 7501 portable gravity operated eyewash shall include a FDA approved high-density green polyethylene 9-gallon tank, ABS plastic eyewash heads with .4 gpm flow rate over 15 minutes, yellow pull-down activation arm, integral handle on top, wide-fill threaded cap, label-mounted operating and maintenance instructions, stainless steel wall bracket (unit must be hung), and 1 bottle of bacteriostatic additive to permit storage of water for six months.

APPLICATIONS

Where the eyes of any person may be exposed to injurious or corrosive materials, when suitable facilities for quick flushing of the eyes needs to be provided and a continuous supply of water is not available. Although the 7501 may be installed in a wide variety of locations, it is ideal for the remote and low traffic areas where protective measures are still needed. Emergency eyewash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7501 is certified by CSA & IAPMO to meet the ANSI Z358.1-2009 Standard for Emergency Eyewash and Shower Equipment.