

# 8200

## Combination Units



### FEATURES & BENEFITS

#### Quality Control

Eye/face wash and valve assembly is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time.

#### Flow Controls

AXION MSR™ ABS plastic showerhead and Omni-Flo wrap-around eye/face wash assembly equipped with integral 20 gpm flow shower control and built in 6.25 gpm flow eye/face wash control allow both parts of the equipment to be safely used simultaneously. Flow controls provide the optimal water flow for a superior coverage area.

#### Construction

1-1/4" Schedule 40 hot-dipped galvanized steel pipe and fittings along with powder-coated cast-iron 9" diameter floor flange provide corrosion resistance in a long lasting product.

#### Valves

Eye/face wash valve is designed to make the flushing of fluid remains occur with the simple push of a stainless steel flag. Shower ball valve is designed to make the flushing of fluid remains occur with the pull of a triangular lever.

#### Protection

Chrome-plated brass in-line 50 x 50 mesh water strainer prevents debris from reaching the eyewash so the unit stays functioning at its best. Strainer is easily serviceable. Yellow plastic dust cover protects the Omni-Flo eye/face wash from debris further optimizing operation.



### SPECIFICATIONS

Model 8200 combination shower and eye/face wash shall include the AXION MSR™ hydrodynamic designed ABS plastic showerhead with self-regulating 20 gpm flow control, green ABS plastic bowl, ABS plastic Omni-Flow wrap around eye/face wash with integral dust cover, chrome-plated brass in-line 50 x 50 mesh water strainer, and chrome-plated brass stay-open shower and eyewash ball valves equipped with stainless steel ball and stem. Unit shall also include powder-coated cast-iron 9" diameter floor flange, universal sign, 21" self-adhesive high visibility Safety Green and bright yellow stripe, and 1-1/4" IPS supply.

### OPTIONS

- Hose & Spray Unit: Model 8901RFK, body spray unit with Feather-Flo ABS plastic head, stay open squeeze lever valve, 8 foot hose, and installation kit.
- Tempered Water Blending Systems: Model TWBS.SH, prepackaged, fully engineered and tested system for mixing hot and cold water to provide tempered water up to 40 gpm for emergency showers and eyewashes (Pat.# 5,350,112).
- Tempered Water Blending Valves: Model 9202, thermostatic mixing valve that mixes hot and cold water for the tempering of shower units at a maximum flow rate of 40 gpm.
- Shower Head: Model 8127FC, corrosion-resistant 10-1/2" stainless steel showerhead with integral 20 gpm flow control.

To see all options for this model, visit [www.hawsc.com](http://www.hawsc.com).

### APPLICATIONS

Where the eyes, face, or body of any person may be exposed to injurious or corrosive materials, suitable facilities for quick drenching and cleansing of the eyes, face, and body shall be provided within the work area for immediate emergency use. Emergency eye/face wash facilities and deluge showers shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 8200 is certified by CSA & IAPMO to meet the ANSI Z358.1-2004 Standard for Emergency Eyewash and Shower Equipment.

