



# model 8309PCP

Laboratory Units

## FEATURES & BENEFITS

### CONSTRUCTION

1-1/4" Schedule 40 polished chrome-plated brass pipe and fittings along with high-polished Type 304 Stainless Steel 9" diameter floor flange provide added corrosion-resistance in a long lasting product.

### FLOW CONTROLS

High polished stainless steel showerhead and Feather-Flo ABS designed eye/face wash heads equipped with integral 20 gpm flow shower control and built 2.5 gpm (2) flow eye/face control allow both parts of the equipment to be safely used simultaneously. Flow controls assure optimal water flow while maintaining a maximum coverage area.

### VALVES

Eye/face wash valve is designed to make the flushing of fluid remains occur with the simple push of a stainless steel flag. Shower ball valve is designed to make the flushing of fluid remains occur with the pull of a triangular lever.

### DUST COVERS

Green ABS flip-top dust covers that release with water pressure keep the unit protected from debris up until the last second before use further optimizing operation.

### QUALITY CONTROL

Eye/face wash and valve assembly is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time.

### SAFETY

8" x 10-3/4" universal combination emergency sign and 21" self-adhesive high visibility stripe in Safety Green and bright yellow make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.



## SPECIFICATIONS

Model 8309PCP polished-chrome finish combination shower and eye/face wash shall include a stainless steel 10-1/2" shower head with integral self-regulating 20 gpm flow control, stainless steel 11" round bowl, stainless steel eyewash yoke assembly with green ABS plastic eye/face wash heads with integral flow controls and dust covers, and chrome-plated brass stay-open shower and eyewash ball valves equipped with stainless steel ball and stem. Unit shall also include polished-chrome brass pipe and fittings, polished stainless steel cast 9" floor flange, polished-aluminum foot treadle, universal sign, and 1-1/4" IPS supply.

## OPTIONS

- Alarm: Model 9001, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a double pole, double throw flow switch.
- Alarm: Model 9001EXP 120 VAC Class 1, Division 2, Groups B, C, and D emergency alarm system. Buzzer and flashing light are activated by an 1-1/4" double pole, double throw flow switch.
- Shower Test Kit: Model 9010 shower test kit includes holding rod, upper corrosion-resistant ring to encircle the shower head, and Tyvek waterproof tunnel shaped tube to guide the water column to container or drain.
- Universal Sign: Model 9020 green and yellow ABS plastic 3-sided high visibility sign.

To see all options for this model, visit [www.hawasco.com](http://www.hawasco.com)

## APPLICATIONS

Where the eyes, face, or body of any person may be exposed to injurious or corrosive materials, suitable facilities for quick drenching or flushing of the eyes, face, and body shall be provided within the work area for immediate emergency use. Emergency eye/face wash facilities and deluge showers shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 8309PCP is certified by CSA & IAPMO to meet the ANSI Z358.1-2009 Standard for Emergency Eyewash and Shower Equipment.