APPLICATION:	PRODUCT NAME:
	8" BACKSPLASH CONTROL VALVE SWIVEL OUTLET
JOB NAME:	SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS
QUANTITY: ITEM NO.	MODEL:
[305mm] 8" [204mm]	MODEL: ■ 13153 OPTIONS OR MODIFICATIONS: □ SUPPLY LINES (24" OR 36") CIRCLE LENGTH □ ELBOWS □ HANDLES (CROSS OR WRIST) CIRCLE STYLE □ VANDAL RESISTANT KIT □ OTHER □ OTHER FEATURES CONTROL VALVE * 8" C/C BACKSPLASH MOUNT * HOT SIDE STEM - RIGHT HAND * COLD SIDE STEM - LEFT HAND * SWIVELLING SEAT DISKS * STAINLESS STEEL SEATS * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE: 200 PSI MAX. STATIC SHIPPING WEIGHT
ROUGH-IN:	* 4.0 LBS
2-1/4" [57mm] 1-3/8" [35mm] 1/2 NPT (2 PL) [22mm] 8" [203mm]	

APPLICATION:		PRODUCT NAME:
		8" BACKSPLASH CONTROL VALVE SWIVEL OUTLET
JOB NAME:		SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS
QUANTITY:	ITEM NO.	MODEL: ■ 13161
12 [305r	" nm]	OPTIONS OR MODIFICATIONS: SUPPLY LINES (24" OR 36") CIRCLE LENGTH ELBOWS HANDLES (CROSS OR WRIST) CIRCLE STYLE VANDAL RESISTANT KIT OTHER
[204mm]		FEATURES CONTROL VALVE * 8" C/C BACKSPLASH MOUNT * INTERNAL SPRING LOADED CHECK VALVES * HOT SIDE STEM - RIGHT HAND * COLD SIDE STEM - LEFT HAND * SWIVELLING SEAT DISKS * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE: 200 PSI MAX. STATIC
ROUGH-IN:		SHIPPING WEIGHT * 4.0 LBS
2-1/4" [57mm] 1-3/8" [35mm] 1/2 NPT (2 PL) [22mm] 8" [203mm]		

SPEC. 13161 REV. A

APPLICATION:		PRODUCT NAME:
		8" BACKSPLASH CONTROL VALVE RIGID OUTLET
JOB NAME:		SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS
QUANTITY:	ITEM NO.	MODEL: ■ 13188
12" ————————————————————————————————————		OPTIONS OR MODIFICATIONS: □ SUPPLY LINES (24" OR 36") CIRCLE LENGTH □ ELBOWS □ HANDLES (CROSS OR WRIST) CIRCLE STYLE □ VANDAL RESISTANT KIT □ OTHER
88 [204		CONTROL VALVE * 8" C/C BACKSPLASH MOUNT * HOT SIDE STEM - RIGHT HAND * COLD SIDE STEM - LEFT HAND * SWIVELLING SEAT DISKS * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE: 200 PSI MAX. STATIC
ROUGH-IN:		SHIPPING WEIGHT * 4.0 LBS
2-1/4" [57mm] 1/2" SLIP JO (2 PL)	1-3/8" [35mm] — 1/2 NPT (2 PL) Ø7/8" [22mm]	
		FISHER MANUFACTURING COMPANY

ANSI/A112.18.1M

TOLL FREE: 800-421-6162 - FAX: 800-832-8238

information@fisher-mfg.com - www.fisher-mfg.com

SPEC. 13188 REV. A

APPLICATION:		PRODUCT NAME:
		8" BACKSPLASH CONTROL VALVE RIGID OUTLET
JOB NAME:		SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS
QUANTITY:	ITEM NO.	MODEL: ■ 13196
[305mm] 8" [204mm]		OPTIONS OR MODIFICATIONS: SUPPLY LINES (24" OR 36") CIRCLE LENGTH ELBOWS HANDLES (CROSS OR WRIST) CIRCLE STYLE VANDAL RESISTANT KIT OTHER
		FEATURES CONTROL VALVE * 8" C/C BACKSPLASH MOUNT * INTERNAL SPRING LOADED CHECK VALVES * HOT SIDE STEM - RIGHT HAND * COLD SIDE STEM - LEFT HAND * SWIVELLING SEAT DISKS * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE: 200 PSI MAX. STATIC
ROUGH-IN:		SHIPPING WEIGHT * 4.0 LBS
2-1/4" [57mm] 1-3/8" [35mm] 1/2 NPT (2 PL) [22mm] 8" [203mm]		
		FISHER MANUFACTURING COMPANY

ANSI/A112.18.1M

TOLL FREE: 800-421-6162 - FAX: 800-832-8238

information @ fisher-mfg.com-www.fisher-mfg.com

SPEC. 13196 REV. A