

# SPEAKMAN® SE-609

## Combination Shower with Rectangular Eye/Face Wash Bowl

### EYE/FACE WASH FEATURES: (SE-400)

- (6) brass chrome-plated aerated sprays
- Yellow polypropylene shrouds.
- Brass, chrome-plated in-line strainer
- ½ in. NPT female brass chrome plated valve
- Stainless steel push handle activator
- ½ in. NPT female inlet
- 9.3 gpm @ 30 psi
- Universal emergency sign included

### SHOWER FEATURES:

- 8 in. diameter yellow plastic showerhead
- Internal 20 gpm flow control
- 1 ½" NPT female brass frost proof valve
- Stanchion is 1 ¼ in. galvanized steel piping and fittings.
- 42" standard bury depth
- Push handle activator
- 1 ¼" NPT female waste
- 20 gpm @ 30 psi

### FINISHES:



DuraJade™ powder-coated galvanized steel (standard)

### COMPLIANCE:

- Certified to ANSI/ISEA Z358.1

### OPTIONS:

Add suffix to model #

- |   |                                 |
|---|---------------------------------|
| • Anti-freeze protection valve                | <input type="checkbox"/> -FPV   |
| • Hand & foot operation                       | <input type="checkbox"/> -HFO   |
| • Hand-held spray                             | <input type="checkbox"/> -HS    |
| • Self-closing shower valve with chain & ring | <input type="checkbox"/> -SCSV  |
| • Stainless steel pull rod                    | <input type="checkbox"/> -SPR   |
| • Anti-scald protection valve                 | <input type="checkbox"/> -SPV   |
| • 1 in. IPS stainless steel ball valve        | <input type="checkbox"/> -SSBV1 |
| • ½ in. IPS stainless steel ball valve        | <input type="checkbox"/> -SSBV2 |
| • Stainless steel showerhead                  | <input type="checkbox"/> -SSH   |

### NOTE:

- The maximum "static" pressure allowable for this unit is 80 psi

### WARRANTY:

- 3 year limited



**DIMENSIONS:** NOTE: 1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice.

