



Built-in Showers with Concealed Supplies

Specifications

Materials

All exposed materials are stainless steel or chrome-plated brass. Valve bodies are cast brass.

Standard Equipment

Supply Inlets

Female supply inlets are 1/2".

Optional Equipment

In-Wall Shower Valve as Selected

For more information on each valve type, please enter the model number in the search box at www.bradleycorp.com.

Showerhead – 1/2" NPT

Institutional or deluxe type chrome-plated showerhead with bent arm and flange or wall arm.

Flow Control

A 1.5 GPM (5.7 LPM) flow control is standard. Actual flow may vary, but will not exceed 2.0 GPM (7.6 LPM) max.

Hand Shower

For more information on each hand shower type, please reference the Hand Showers tech data at www.bradleycorp.com.

Diverter Valve

Lever handle operation for easy transfer of water flow between fixed and hand-held shower. ADA compliant.

Tub Spout

Diverter type spout with 1/2" inlet.

Showerhead Anchor Plate

3/16" cadmium-plated steel plate furnished with countersunk mounting holes and machine screws provide additional mounting length.

Showerhead Back Plate

3/16" cadmium-plated steel plate furnished with couplings, studs and nuts allows most secure anchorage of wall-mounted components.





Built-in Showers with Concealed Supplies

| Model | Description |
|---|--|
| <input type="checkbox"/> 1C | Built-In Showers with Concealed Supplies |
| Optional Selections | |
| Valve Type (select one): | |
| Hot/tempered and cold supplies | |
| <input type="checkbox"/> EF | Equa Flo Pressure Balancing Valve |
| <input type="checkbox"/> EFT1 | Equa Flo Pressure Balancing Valve with Temperature Display |
| <input type="checkbox"/> C5 | Equa-Flo C5 Pressure-Balancing Valve |
| <input type="checkbox"/> HD | Equa Flo HD Pressure Balancing |
| <input type="checkbox"/> HDT1 | Equa Flo HD Pressure Balancing Valve with Temperature Display |
| <input type="checkbox"/> TMV | Thermostatic Mixing Valve |
| <input type="checkbox"/> TMVT1 | Thermostatic Mixing Valve with Temperature Display |
| <input type="checkbox"/> HC | Hot and Cold Compression Valve |
| Single tempered/cold supply | |
| <input type="checkbox"/> AST | Air Pushbutton |
| <input type="checkbox"/> PM | Presto 50B |
| <input type="checkbox"/> TTPA | TouchTime Pushbutton* |
| <input type="checkbox"/> TTPB | TouchTime Piezo Switch* |
| <input type="checkbox"/> NONE | No Valve |
| Supply Stop Type (select one): | |
| (included with EF, HD, TMV, EFT1, HDT1, TMVT1 and C5 valves) | |
| <input type="checkbox"/> ST | Stops in Supply for Valves |
| <input type="checkbox"/> NONE | No Supply Stops |
| Showerhead Type (select one): | |
| Bent Arm and Flange | |
| <input type="checkbox"/> S115 | Standard Showerhead (Flow Rate = 1.5 GPM/5.7 LPM) |
| <input type="checkbox"/> S120 | Standard Showerhead (Flow Rate = 2.0 GPM/7.6 LPM) |
| <input type="checkbox"/> ES1 | Economy Soft Flow w/ Ball Joint (Flow Rate = 2.0 GPM/7.6 LPM) |
| <input type="checkbox"/> D1 | Deluxe Showerhead w/ Ball Joint (Flow Rate = 1.5 GPM/5.7 LPM) |
| <input type="checkbox"/> J1 | Multi-Jet Showerhead w/ Ball Joint (Flow Rate = 1.5 GPM/5.7 LPM) |
| <input type="checkbox"/> LX1 | Luxury Showerhead w/ Ball Joint (Flow Rate = 1.5 GPM/5.7 LPM) |
| <input type="checkbox"/> B1 | Axis Showerhead w/ Ball Joint (Flow Rate = 1.5 GPM/5.7 LPM) |
| Wall Arm | |
| <input type="checkbox"/> S15 | Standard Showerhead (Flow Rate = 1.5 GPM/5.7 LPM) |
| <input type="checkbox"/> SX15 | Severe Service Showerhead (Flow Rate = 1.5 GPM/5.7 LPM) |
| <input type="checkbox"/> S20 | Standard Showerhead (Flow Rate = 2.0 GPM/7.6 LPM) |
| <input type="checkbox"/> SX20 | Severe Service Showerhead (Flow Rate = 2.0 GPM/7.6 LPM) |
| <input type="checkbox"/> SF | Deluxe Showerhead w/ Ball Joint (Flow Rate = 1.5 GPM/5.7 LPM) |
| <input type="checkbox"/> ES | Economy Soft Flow w/ Ball Joint (Flow Rate = 2.0 GPM/7.6 LPM) |
| <input type="checkbox"/> J | Multi-Jet Showerhead w/ Ball Joint (Flow Rate = 1.5GPM/5.7 LPM) |
| <input type="checkbox"/> LX | Luxury Showerhead w/ Ball Joint (Flow Rate = 1.5GPM/5.7 LPM) |
| <input type="checkbox"/> B | Axis Showerhead w/ Ball Joint (Flow Rate = 1.5GPM/5.7 LPM) |
| <input type="checkbox"/> NONE | No Showerhead |

| |
|--|
| Showerhead Options (select one): |
| Volume Control Type (only available on S15, S20, S115 and S120 showerheads): |
| <input type="checkbox"/> AKV Allen Key Volume Control |
| <input type="checkbox"/> LHV Lever Handle Volume Control |
| <input type="checkbox"/> NONE No Volume Control |
| Ball Joint Type (only available on S15, S20, S115 and S120 showerheads): |
| <input type="checkbox"/> LBJ Lockable Ball Joint |
| <input type="checkbox"/> NONE No Ball Joint |
| Hand Shower Type** (select one): |
| <input type="checkbox"/> A24 With 60" flexible hose, 24" ADA Grab Bar and Vacuum Breaker |
| <input type="checkbox"/> A36 With 60" flexible hose, 36" ADA Grab Bar and Vacuum Breaker |
| <input type="checkbox"/> B24 With 60" Flexible Hose, 24" Metal Slide Bar and Vacuum Breaker |
| <input type="checkbox"/> B-30 With 60" flexible hose, 30" Slide Bar |
| <input type="checkbox"/> E24 With 60" Flexible Hose, 22" Economy Slide Bar and Vacuum Breaker |
| <input type="checkbox"/> HW With 60" Flexible Hose, Wall Hooks and Vacuum Breaker |
| <input type="checkbox"/> HS With 60" Flexible Hose, Wall Hooks, Vacuum Breaker and Quick Disconnect |
| <input type="checkbox"/> SB With 60" Flexible Hose, 24" Metal Slide Bar, Vacuum Breaker and Quick Disconnect |
| <input type="checkbox"/> SB-30 With 60" flexible hose, 30" Slide Bar and Quick Disconnect |
| <input type="checkbox"/> NONE No Hand Shower |
| Diverter Valve Type (select one): |
| <input type="checkbox"/> DV In-Wall Diverter Valve |
| <input type="checkbox"/> NONE No Diverter Valve |
| Tub Spout Type (select one): |
| <input type="checkbox"/> TS Tub Spout — threaded |
| <input type="checkbox"/> DJ Tub Spout — slip joint |
| <input type="checkbox"/> NONE No Tub Spout |
| Soap Dish Type (select one): |
| <input type="checkbox"/> SD Wall Mounted Soap Dish |
| <input type="checkbox"/> RSD Recessed Soap Dish |
| <input type="checkbox"/> NONE No Soap Dish |
| Showerhead Anchor Plate Type (select one): |
| <input type="checkbox"/> AP Anchor Plate for Showerhead*** |
| <input type="checkbox"/> NONE No Anchor Plate for Showerhead |
| Showerhead Back Plate Type (select one): |
| <input type="checkbox"/> BP Back Plate for Showerhead*** |
| <input type="checkbox"/> NONE No Back Plate for Showerhead |

*TTPA and TTPB valves require a low-voltage UL/CSA listed 120VAC/12VDC plug-in adapter.

** All Hand Showers are 1.5 GPM (5.7 LPM).

*** Only available with wall arm showerheads.

Consult local and national codes: conformity and compliance to local and national codes is the responsibility of the installer.